



D4.4 FIWARE4_Intelligent Control for Wastewater Treatment

Authors: Alex van der Helm (WNT), Marcel Zandvoort (WNT) and Siddharth Seshan (KWR)

Co-Authors: Maarten van Duren (WNT), Dimitris Amoiridis (WNT), Lluís Echeverria (EUT), Dirk Vries (KWR)

April / 2022



This project has received funding from the European Union's Horizon 2020 research and innovation programme under Grant agreement No. 821036.



Disclaimer

This document reflects only the author's view. The European Commission is not responsible for any use that may be made of the information it contains.

Intellectual Property Rights

© 2022, Fiware4Water consortium

All rights reserved.

This document contains original unpublished work except where clearly indicated otherwise. Acknowledgement of previously published material and of the work of others has been made through appropriate citation, quotation or both.

This document is the property of the Fiware4Water consortium members. No copying or distributing, in any form or by any means, is allowed without the prior written agreement of the owner of the property rights. In addition to such written permission, the source must be clearly referenced.

Project Consortium



Executive Summary

Waternet's (WNT) wastewater treatment plant (WWTP) Amsterdam West has a capacity of 1 Million population equivalent and serves the city of Amsterdam. The process automation (PA) of WWTP Amsterdam and the IT architecture of WNT is in continuous development to allow the support of upcoming technologies such as Artificial Intelligence (AI), Internet of Things (IoT), Business Intelligence (BI) and streaming analytics to improve operational efficiency and asset management, and to reduce climate impact and costs.

Currently the control loops of WWTP Amsterdam West are for a large part locally distributed and dedicated to a single wastewater treatment unit process. The objective is to demonstrate the integration of the Fiware4Water architecture (F4W) using FIWARE in the legacy system with better use of real-time plant data and the use of data-driven AI smart applications in practice, to achieve a more optimal plant-wide control with respect to its climate footprint and costs while meeting effluent quality criteria.

To meet the objective, one of the seven parallel treatment lanes at WWTP Amsterdam West is made available as a full-scale research lane for the F4W project. In this research lane additional sensors are deployed and integrated, and an on-site research facility is built to gain more insight in the wastewater treatment process. Furthermore the F4W architecture is deployed and integrated in the WNT legacy system, including (near) real-time (ranging from no delay up to maximum of 2 minutes delay) F4W WWTP AI smart applications developed in Deliverable 3.3, and F4W data models developed in Deliverable 2.3. Finally intelligent real-time AI control is implemented in the legacy system. The F4W AI smart applications deployed are software (soft) sensors for determining the influent flow per lane, for prediction of the influent flow and for determining the airflow per lane. A soft sensor, for this case, can be defined as a virtual sensor, whose output is based on (AI) calculation of multiple observed measurements. Next to the soft sensors an AI smart application for (near) real-time data validation is deployed. The implemented AI control model has a control objective to minimise nitrous oxide (N_2O) emissions and energy consumption at minimum costs whilst meeting effluent water quality targets. Half of the WNT climate footprint is determined by nitrous oxide emissions of the WWTPs. Thus, minimising N_2O emission has a large impact on GHG emissions reduction and optimal control of these emissions is therefore considered to be of key importance in reaching climate neutrality.

From the Amsterdam demo case it can be concluded that F4W architecture can be integrated in a water utility legacy system with AI smart applications running in (near) real-time. Furthermore it is possible to use real-time AI control for optimizing nitrous oxide emissions and energy for wastewater treatment plants in practice. By integrating in the legacy systems that end users are used to work with on a daily basis, it is very easy for them to access and use the smart applications in their work. For the wastewater technologists, one of the end users of soft sensors, there is no difference whether the treatment plant data is from physical sensors or AI soft sensors and whether it comes from the legacy system or from F4W. The same holds true for the use of the control model by the plant operators. By integrating the activation, deactivation, safety constraints and automatic fallback of the AI control in the existing legacy user interface (UI), the AI control is an additional option next to manual and automatic control in the legacy distributed control system (DCS). This has the big advantage that there is no additional training necessary for operating personnel for using new additional UI/systems and identity access management (IAM) is secured in existing processes.

WWTPs are used throughout Europe and the world. They can differ in size, type of treatment processes, level of automation, type of sensors, operation etc. So although the potential for WWTP AI

smart applications is enormous, not all of developed WWTP smart applications can be used directly at any WWTP in Europe. For instance the influent soft sensor per lane is very specific for the plant layout and sensor setup of WWTP Amsterdam West. However, the AI data validation model is highly generic and can be trained for other WWTPs and for other sensors. Also the AI influent flow prediction using rain meter data can be trained for WWTPs at other locations. The control model is applied at the research lane, one of the seven treatment lanes of WWTP Amsterdam West, and can also be implemented to the other six treatment lanes of WWTP Amsterdam West. The applied approach works, so the AI model architectures can be used for other (WNT) WWTPs with practical adaptations (e.g. including or excluding of other (soft) sensors) and model training.

The F4W Amsterdam demo case demonstrates the possibilities for the use of FIWARE in the (waste)water sector. The interoperable properties of the FIWARE-enabled F4W architecture together with the developed F4W data models, enable replication and upscaling. The methodologies, approaches, and developed technologies in the Amsterdam demo case present a successful baseline to guide other water utilities for future digitalization processes. By closely working together in developing the AI models, integrating the AI models and deploying the AI models at WWTP Amsterdam West, WNT, KWR and EUT collaborated transnational in the most extensive way. In F4W the complimentary knowledge on wastewater treatment, sensing, AI and model deployment from research and practice perspective were brought together. The complementary collaboration made the development of the smart applications, the integration of the F4W architecture in the legacy system and the use of the smart applications for WWTPs possible in practice. The knowledge development on AI in the water sector for the demo case can be used across Europe.

The European added value (EAV) of Deliverable 4.4 is not only in boosting the excellence in AI for the water sector, but also in the knowledge developed regarding nitrous oxide emissions reduction in practice. The F4W project has boosted the knowledge and research about the formation and reduction of N₂O emissions from WWTPs. Also data sets are being extended on N₂O emissions for future use. Therefore it contributes to sustainability and greenhouse gas emissions reduction ambitions of the EU. The demo case Amsterdam West WWTP is therefore directly contributing to the acceleration of the twin – green and digital – transition, which is seen as a necessity in order to reach the climate goals by 2030. The EAV and recommendations are further detailed in the conclusion and perspectives section.

The use of the soft sensors and the AI control model were well received by WNT wastewater technologists and process operators. However, at the time of completion of the present deliverable the AI control model tested was the first version that mimics the current control. The tests with the optimized control agent are done in the last month of the project, so the results are not available before finalization of this deliverable. However, operational personnel stated that since the control agent is very well capable of mimicking the current legacy control in practice, and after seeing the results of the final control agent in off-line tests, the expectations are that it will be able to improve the current operation with regard to nitrous oxide emissions and energy use.

Related Deliverables

- D1.1** Requirements from Demo Cases
- D2.1** Specification of system architecture for water consumption and quality monitoring
- D2.2** Extensions of FIWARE ecosystem with Big Data and AI frameworks
- D2.3** Extension of FIWARE for supporting water management and quality monitoring use-cases
- D3.3** FIWARE-enabled applications for wastewater treatment

Document Information

Programme	H2020 – SC0511-2018
Project Acronym	Fiware4Water
Project full name	FIWARE for the Next Generation Internet Services for the WATER sector
Deliverable	D4.4: FIWARE4_Intelligent Control for Wastewater Treatment
Work Package	WP4: Demonstrating Fiware4Water in the Real (Water) World
Task	Task 4.3: FIWARE4_Intelligent Control for Wastewater Treatment in the Netherlands
Lead Beneficiary	Waternet (WNT)
Author(s)	Alex VAN DER HELM (WNT), Marcel ZANDVOORT (WNT) and Siddharth SESHAN (KWR)
Contributor(s)	Maarten van DUREN (WNT), Dimitris AMOIRIDIS (WNT), Lluís ECHEVERRIA (EUT) and Dirk VRIES (KWR)
Quality check	Fernando Lopez (FF)
Planned Delivery Date	M35 30/04/2022
Actual Delivery Date	M35 30/04/2022
Dissemination Level	Confidential (Information available in the Grant Agreement)

Revision history

Version	Date	Author(s)/Contributor(s)	Notes
Draft1	18/04/2022	Alex VAN DER HELM (WNT) / Marcel ZANDVOORT (WNT) / Maarten van DUREN (WNT), Siddharth SESHAN (KWR), Dimitris AMOIRIDIS (WNT), Lluís ECHEVERRIA (EUT), Dirk VRIES (KWR)	
Final draft	22/04/2022		Internal review by Alberto ABELLA (FF)
Final	29/04/2022	Alex VAN DER HELM (WNT) / Marcel ZANDVOORT (WNT)	

Table of Contents

Executive Summary	3
Table of Contents	7
List of figures	9
List of Acronyms	11
I. Introduction.....	12
II. Full Demo Case Description	13
II.1. Amsterdam West WWTP	13
II.2. Plant Layout	13
III. Sensor Deployment	15
III.1. On-site electrical and data infrastructure extensions	15
III.2. On-site research facility.....	17
III.3. Aeration tank sensors.....	18
III.4. Secondary clarifier sensors	19
IV. F4W architecture integration in legacy system	20
IV.1. Legacy control system	20
IV.2. F4W architecture WWTP Amsterdam West	20
IV.3. F4W AI airflow soft sensor integrator	23
IV.4. F4W AI-based data validation.....	23
IV.5. FIWARE Smart Legacy Connector	24
V. Smart applications in practice	26
V.1. Influent flow soft sensor per lane	26
V.2. Influent flow prediction	28
V.3. Airflow soft sensor per lane	28
V.4. Real-time Data Validation	33

VI.	Intelligent control in practice	35
VI.1.	Real-time off-line testing	35
VI.2.	Real-time on-line testing	37
VII.	User interfaces	40
VII.1.	Data validation and soft-sensors UI	40
VII.2.	Control model UI.....	43
VIII.	Conclusion and Perspectives	45
VIII.1.	Demo case Amsterdam West WWTP	45
VIII.2.	European added value (EAV) and upscaling	46

List of figures

Figure 1: WWTP Amsterdam West.....	12
Figure 2: Aerial view of the WWTP and the research lane, aeration tank (closed circular tank, red circle) and the secondary clarifiers (open circular tanks, red ellipse). The red squares indicate the location of the N ₂ O measurement (upper and lower small squares), the influent sampling location (middle small square) and the research facility (large square).....	14
Figure 3: Schematic overview of the waterline of WWTP Amsterdam West, more specific the research lane, (1) screens for removal of large particles, (2) primary clarifier (one of four), (3) distribution works, (4) aeration tank (one of seven), (5) secondary clarifier (one of two per lane) (6) the research facility constructed for this research	14
Figure 4: Screenshots of the research lane in the polymer dosing DCS system (top pictures), control cabinets (bottom left and right) and cable tray alongside the air pipe (bottom centre).....	16
Figure 5: Overview of the research facility, sensors and analyzers are indicated on top (in Dutch). On the right the distribution works from where pre-settled wastewater is transported to the flow-through vessel (black box outside the research facility). The UF is located in the centre of the research facility, the analyzers are wall mounted	17
Figure 6: Overview of the aeration tank (in Dutch). On the right the lava filters and N ₂ O analyser. (additional) sensors are indicated at the top	18
Figure 7: Overview of the secondary clarifier (right) and the sludge return (Archimedes screws on the left), all sensors are research lane specific (in Dutch).....	19
Figure 8: Detailed architecture of the F4W setup and the connections between the components	21
Figure 9: Schematic overview of the Integration of F4W architecture with the legacy control system	22
Figure 10: Schematic overview FIWARE Enabling and Integration of the AI-based Data Validation Application.....	24
Figure 11: Schematic representation of flows at WWTP Amsterdam West	26
Figure 12: Example of real-time results from the influent flow soft sensor per lane	27
Figure 13: Schematic representation of process air flows to the 7 aeration tanks at WWTP Amsterdam West	28
Figure 14: Example of real-time results from the AI airflow soft sensor for lanes 1 to 7	29
Figure 15: Example of backfill for of soft sensor air flow for lane 5 (brown line) and the measured sensor value of the air flow for lane 5 (pink line)	30
Figure 16: Example of backfill for of soft sensor air flow for lane 2 (blue line) and the measured sensor value of the air flow for lane 2 (red line).....	30
Figure 17: Example of the evaluation of the soft sensor air flow for lane 2 (blue line) with newly installed air flow pitot tube measurement (purple line) and the measured value of the existing air flow sensor for lane 2 (red line).....	31
Figure 18: Results of Grafana dashboard of the AI airflow soft sensor	32
Figure 19: AI-based Data Validation Application Integrated in FIWARE and Implemented in Real-time	33
Figure 20: AI control model setpoint for the oxygen concentration in AT2 (green line) and the measured oxygen concentration in AT2 (dark red line).....	36
Figure 21: Example of an issue during real-time off-line testing in practice, in this case caused by ingesting sensor data that was not automatically adjusted to summer time	36
Figure 22: Example of AI control model taking over the control of the oxygen setpoint of AT2 for several hours (green line) and the measured oxygen concentration in AT2 (dark red line).....	38

Figure 23: “Orange” and “red” safety filters, time dependent watchdog in the legacy DCS system for AI control setpoints 39

Figure 24: Grafana dashboard of the data validation accessible via web browser 41

Figure 25: Part of the Grafana dashboard of the air-flow soft sensor per lane accessible via web browser, top 2 rows represent input data of the air valves and bottom 2 rows represent soft sensor output values for the air flow and energy per lane 42

Figure 26: Example of a dashboard made, in this case for the influent wastewater, in TrendMiner... 43

Figure 27: DCS UI for oxygen control setpoint (“zuurstofsetpoint”) extended with “Datalab” option for AI control, set to “AUTO” for automatic control by the DCS 44

Figure 28: DCS UI for oxygen control setpoint (“zuurstofsetpoint”) extended with “Datalab” option for AI control, set to “Datalab” for AI control..... 44

List of Acronyms

AI	Artificial Intelligence
ANN	Artificial Neural Network
AT	Aeration Tank
BI	Business Intelligence
DCS	Distributed Control System
DL	Deep Learning
DVR	Data Validation and Reconciliation
EAV	European added value
F4W	Fiware4Water project
FAT	Factory Acceptance Test
FEWS	Flood Early Warning System
IoT	Internet of Things
JSON	JavaScript Object Notation
LSTM	Long Short-Term Memory
NaN	Not a Number
NGSI-LD	Next Generation Service Interface for Linked Data
PA	Process Automation
PID	Proportional, Integral, Derivative
PIMS	Process Information Management System
PLC	Programmable Logic Controller
RAS	Return Activated Sludge
SAT	Site Acceptance Test
SCADA	Supervisory Control and Data Acquisition
UF	UltraFiltration membrane
VM	Virtual Machine
WAS	Waste Activated Sludge
WPL	Work Packages Leaders
WWTP	Wastewater treatment plant